

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 1 of 13  
Print date: 26/10/2020

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: PROFEC CLEANER

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

INDUSTRIAL SOLVENT  
CLEANING PRODUCT FOR ADHESIVES AND MATERIALS

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **ADHESIVOS KEFREN, S.A.**  
Address: Calle del Dolar, Parcela 148. P.I. Las Atalayas. Buzón 20.078  
City: ALICANTE  
Province: 03114- Alicante (ESPAÑA)  
Telephone: +34 965116961  
Fax: +34 965116962  
E-mail: kefren@adhesivoskefren.com  
Web: www.adhesivoskefren.com

1.4 Emergency telephone number: +34 915620420 (Available 24 hours)  
UFI: A97F-ED88-M12V-J6VU

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:  
Eye Irrit. 2 : Causes serious eye irritation.  
Flam. Liq. 2 : Highly flammable liquid and vapour.  
STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

H statements:

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

P statements:

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 2 of 13  
Print date: 26/10/2020

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO <sub>2</sub> , chemical foam or dusty. Never use water.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains:

acetone, propan-2-one, propanone  
butanone, ethyl methyl ketone

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01-2119471330-49-XXXX	[1] acetone, propan-2-one, propanone	20 - 100 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone, ethyl methyl ketone	20 - 50 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 3 of 13  
Print date: 26/10/2020

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### **Eye contact.**

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

## **SECTION 5: FIREFIGHTING MEASURES.**

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Suitable extinguishing media:**

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the substance or mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 4 of 13  
Print date: 26/10/2020

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

#### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 5 of 13  
Print date: 26/10/2020

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
acetone, propan-2-one, propanone	67-64-1	European Union [1]	Eight hours	500	1210
			Short term		
		United Kingdom [2]	Eight hours	500	1210
			Short term	1500	3620
		Éire [3]	Eight hours	500	1210
			Short term		
		United States [4] (Cal/OSHA)	Eight hours	500	
			Short term	750 (Ceiling) 3000	
		United States [5] (NIOSH)	Eight hours	250	
			Short term		
		United States [6] (OSHA)	Eight hours	1000	2400
			Short term		
butanone, ethyl methyl ketone	78-93-3	European Union [1]	Eight hours	200	600
			Short term	300	900
		United Kingdom [2]	Eight hours	200	600
			Short term	300	899
		Éire [3]	Eight hours	200	600
			Short term	300	900
		United States [4] (Cal/OSHA)	Eight hours	200	
			Short term	300	
		United States [5] (NIOSH)	Eight hours	200	
			Short term	300	
		United States [6] (OSHA)	Eight hours	200	590
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1210 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	200 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	2420 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	186 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	62 (mg/kg bw/day)

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 6 of 13  
Print date: 26/10/2020

butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (General population)	Oral, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)
	soil	29,5 (mg/kg soil dw)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
oral (Hazard for predators)	1000 (mg/kg food)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 7 of 13  
Print date: 26/10/2020

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>INDUSTRIAL SOLVENT CLEANING PRODUCT FOR ADHESIVES AND MATERIALS</b>		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
<b>Eye protection:</b>			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		
<b>Skin protection:</b>			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 8 of 13  
Print date: 26/10/2020

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: Transparent liquid with characteristic odour

Colour: N.A./N.A.

Odour: Organic Solvents

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: 65 °C

Flash point: -15 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: 167

Vapour density: N.A./N.A.

Relative density: 0.80

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

#### 9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

At high temperatures can occur pyrolysis and dehydrogenation.

#### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.

#### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 9 of 13  
Print date: 26/10/2020

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
acetone, propan-2-one, propanone  CAS No: 67-64-1 EC No: 200-662-2	Oral	LD50	Rat	5800 mg/kg bw [1]
	Dermal			
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 10 of 13  
Print date: 26/10/2020

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
acetone, propan-2-one, propanone  CAS No: 67-64-1      EC No: 200-662-2	Fish	LC50	Fish	8300 mg/l (96 h) [1] [1] Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8
	Aquatic invertebrates	LC50	Crustacean	8450 mg/l (48 h) [1] [1] Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217. Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)
	Aquatic plants	EC50	Algae	7200 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
butanone, ethyl methyl ketone  CAS No: 78-93-3      EC No: 201-159-0	0,29	-	-	Very low

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 11 of 13  
Print date: 26/10/2020

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1993

### 14.2 UN proper shipping name.

Description:

ADR: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL METHYL KETONE), 3, PG II, (D/E)

IMDG: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL METHYL KETONE), 3, PG II (-15°C)

ICAO/IATA: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL METHYL KETONE), 3, PG II

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: II

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 3

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 12 of 13  
Print date: 26/10/2020



Hazard number: 33  
ADR LQ: 1 L  
IMDG LQ: 1 L  
ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E  
Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatile organic compound (VOC)

VOC content (p/p): 100 %  
VOC content: 800 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.  
Available Product Exposure Scenario.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## PROFEC CLEANER

Version 1 Date of compilation: 26/10/2020

Page 13 of 13  
Print date: 26/10/2020

Flam. Liq. 2 : Flammable liquid, Category 2  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Available Product Exposure Scenario.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AwSV: Facility Regulations for handling substances that are hazardous for the water.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

## Annex to the extended Safety Data Sheet (eSDS)

Industrial

### Identification of the substance or mixture

**Product definition** : Mono-constituent substance  
**Code** : 35025  
**Product name** : ACETONE

### Section 1 - Title

**Short title of the exposure scenario** : [200-662-2] Uses in Cleaning Agents - Industrial

**List of use descriptors** : **Identified use name:** Use in cleaning agents - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC09, PROC10, PROC13, PROC19  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC04  
**Market sector by type of chemical product:** Not applicable.  
**Article category related to subsequent service life:** Not applicable.

**Environmental contributing scenarios** : **Use in cleaning agents**

**Health Contributing scenarios** : **Use in cleaning agents**

**Processes and activities covered by the exposure scenario** : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### Section 2 - Exposure controls

#### **Contributing scenario controlling environmental exposure for 0: Use in cleaning agents**

**Product characteristics** : Substance is a unique structure., Ketone., Readily biodegradable

**Amounts used** : Annual site tonnage 641

**Frequency and duration of use** : Emission days 360

**Other conditions affecting environmental exposure** : Indoor or outdoor use

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil** : Common practices vary across sites thus conservative process release estimates used.

**Organizational measures to prevent/limit release from site** : Common practices vary across sites thus conservative process release estimates used.

**Conditions and measures related to external treatment of waste for disposal** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Date of issue/Date of revision** : 09/03/2016

**Contributing scenario controlling worker exposure for 0: Use in cleaning agents**

<b>Concentration of substance in mixture or article</b>	: Covers percentage substance in the product up to 100% (unless stated differently).
<b>Physical state</b>	: Liquid, vapour pressure > 10 kPa
<b>Frequency and duration of use</b>	: Covers daily exposures up to 8 hours
<b>Other conditions affecting workers exposure</b>	: Assumes a good basic standard of occupational hygiene is implemented

**Contributing scenarios - Operational conditions and risk management measures**

General exposures (Eye irritation)  
Use suitable eye protection.

General exposures (skin Irritant)  
Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

General exposures (closed systems)  
Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Process sampling Open systems  
No specific measures identified.

Mixing operations (open systems)  
No specific measures identified.

Spraying/fogging by machine application  
Ensure material transfers are under containment or extract ventilation.

Spraying/fogging by machine application  
Ensure operation is undertaken outdoors.

Spraying/fogging by machine application  
Wear a respirator conforming to EN140 with type A/P2 filter or better.

Bulk transfers Non-dedicated facility  
No specific measures identified.

Bulk transfers Dedicated facility  
No specific measures identified.

Small package filling  
No specific measures identified.

Rolling, Brushing  
No specific measures identified.

Equipment cleaning and maintenance  
No specific measures identified.

Dipping, immersion and pouring  
No specific measures identified.

Hand application - fingerpaints, pastels, adhesives  
Wear suitable gloves tested to EN374.

**Conditions and measures related to personal protection and hygiene**

**Section 3 - Exposure estimation and reference to its source**

**Website:** : Not applicable.

**Exposure estimation and reference to its source - Environment: 1: Use in cleaning agents**

**Exposure assessment (environment):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

**Exposure estimation and reference to its source - Workers: 0: Use in cleaning agents**

**Exposure assessment (human):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

**Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES**

**Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Health** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Additional good practice advice beyond the REACH CSA**

**Environment** : Not available.

**Health** : Not available.



## Annex to the extended Safety Data Sheet (eSDS)

Industrial

### Identification of the substance or mixture

**Product definition** : Mono-constituent substance  
**Code** : 35025  
**Product name** : ACETONE

### Section 1 - Title

**Short title of the exposure scenario** : [200-662-2] Uses in Cleaning Agents - Professional

**List of use descriptors** : **Identified use name:** Use in cleaning agents - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC10, PROC11, PROC15, PROC19  
**Sector of end use:** SU22  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08a, ERC08d  
**Market sector by type of chemical product:** Not applicable.  
**Article category related to subsequent service life:** Not applicable.

**Environmental contributing scenarios** : **Use in cleaning agents**

**Health Contributing scenarios** : **Use in cleaning agents**

**Processes and activities covered by the exposure scenario** : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### Section 2 - Exposure controls

#### Contributing scenario controlling environmental exposure for 0: Use in cleaning agents

**Product characteristics** : Substance is a unique structure., Ketone., Readily biodegradable

**Amounts used** : Annual site tonnage 641

**Frequency and duration of use** : Emission days 360

**Other conditions affecting environmental exposure** : Indoor or outdoor use

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil** : Common practices vary across sites thus conservative process release estimates used.

**Organizational measures to prevent/limit release from site** : Common practices vary across sites thus conservative process release estimates used.

**Conditions and measures related to external treatment of waste for disposal** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Date of issue/Date of revision** : 09/03/2016

**Contributing scenario controlling worker exposure for 0: Use in cleaning agents**

<b>Concentration of substance in mixture or article</b>	: Covers percentage substance in the product up to 100% (unless stated differently).
<b>Physical state</b>	: Liquid, vapour pressure > 10 kPa
<b>Frequency and duration of use</b>	: Covers daily exposures up to 8 hours
<b>Other conditions affecting workers exposure</b>	: Assumes a good basic standard of occupational hygiene is implemented

**Contributing scenarios - Operational conditions and risk management measures**

General exposures (Eye irritation)  
Use suitable eye protection.

General exposures (skin Irritant)  
Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

General exposures (closed systems)  
Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Process sampling  
No specific measures identified.

Mixing operations (open systems) With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Mixing operations (open systems)  
Ensure operation is undertaken outdoors.

Mixing operations (open systems)  
Avoid carrying out activities involving exposure for more than 4 hours.

Bulk transfers Non-dedicated facility With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Bulk transfers Non-dedicated facility  
Ensure operation is undertaken outdoors.

Bulk transfers Non-dedicated facility  
Avoid carrying out activities involving exposure for more than 4 hours.

Bulk transfers Dedicated facility  
No specific measures identified.

Small package filling Dedicated facility  
No specific measures identified.

Equipment cleaning and maintenance  
Ensure material transfers are under containment or extract ventilation.

Equipment cleaning and maintenance  
Limit the substance content in the product to 25%.

Equipment cleaning and maintenance  
Avoid carrying out operation for more than 4 hours.

Spraying or fogging With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Spraying or fogging  
Limit the substance content in the product to 25%. Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours.

Spraying or fogging

Avoid carrying out activities involving exposure for more than 1 hour.

Spraying or fogging

Wear a respirator conforming to EN140 with type A/P2 filter or better.

Dipping, immersion and pouring

No specific measures identified.

Hand application - fingerpaints, pastels, adhesives

Limit the substance content in the product to 25%. Wear suitable gloves tested to EN374.

Hand application - fingerpaints, pastels, adhesives

Avoid carrying out operation for more than 1 hour.

#### Conditions and measures related to personal protection and hygiene

### Section 3 - Exposure estimation and reference to its source

**Website:** : Not applicable.

#### Exposure estimation and reference to its source - Environment: 1: Use in cleaning agents

**Exposure assessment (environment):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

#### Exposure estimation and reference to its source - Workers: 0: Use in cleaning agents

**Exposure assessment (human):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

### Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

**Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Health** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

### Additional good practice advice beyond the REACH CSA

**Environment** : Not available.

**Health** : Not available.

## Annex to the extended Safety Data Sheet (eSDS)

Industrial

### Identification of the substance or mixture

**Product definition** : Mono-constituent substance  
**Code** : 35025  
**Product name** : ACETONE

### Section 1 - Title

**Short title of the exposure scenario** : [200-662-2] Uses in Coatings - Industrial

**List of use descriptors** : **Identified use name:** Use in coatings - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC09, PROC10, PROC13, PROC15, PROC19  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC04  
**Market sector by type of chemical product:** Not applicable.  
**Article category related to subsequent service life:** Not applicable.

**Environmental contributing scenarios** : **Coatings**

**Health Contributing scenarios** : **Coatings**

**Processes and activities covered by the exposure scenario** : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### Section 2 - Exposure controls

#### Contributing scenario controlling environmental exposure for 0: Coatings

**Product characteristics** : Substance is a unique structure., Ketone., Readily biodegradable  
**Amounts used** : Annual site tonnage 641  
**Frequency and duration of use** : Emission days 360  
**Other conditions affecting environmental exposure** : Indoor or outdoor use  
**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil** : Common practices vary across sites thus conservative process release estimates used.  
**Organizational measures to prevent/limit release from site** : Common practices vary across sites thus conservative process release estimates used.  
**Conditions and measures related to external treatment of waste for disposal** : External treatment and disposal of waste should comply with applicable local and/or national regulations.  
**Conditions and measures related to external recovery of waste** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Date of issue/Date of revision** : 09/03/2016

**Contributing scenario controlling worker exposure for 0: Coatings**

<b>Concentration of substance in mixture or article</b>	: Covers percentage substance in the product up to 100% (unless stated differently).
<b>Physical state</b>	: Liquid, vapour pressure > 10 kPa
<b>Frequency and duration of use</b>	: Covers daily exposures up to 8 hours
<b>Other conditions affecting workers exposure</b>	: Assumes a good basic standard of occupational hygiene is implemented

**Contributing scenarios - Operational conditions and risk management measures**

General exposures (Eye irritation)  
Use suitable eye protection.

General exposures (skin Irritant)  
Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

General exposures (closed systems)  
Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Process sampling Open systems  
No specific measures identified.

Mixing operations (open systems)  
No specific measures identified.

Spraying/fogging by machine application  
Ensure material transfers are under containment or extract ventilation.

Spraying/fogging by machine application  
Ensure operation is undertaken outdoors.

Spraying/fogging by machine application  
Wear a respirator conforming to EN140 with type A/P2 filter or better.

Bulk transfers Non-dedicated facility  
No specific measures identified.

Bulk transfers Dedicated facility  
No specific measures identified.

Small package filling  
No specific measures identified.

Rolling, Brushing  
No specific measures identified.

Equipment cleaning and maintenance  
No specific measures identified.

Dipping, immersion and pouring  
No specific measures identified.

Hand application - fingerpaints, pastels, adhesives  
Wear suitable gloves tested to EN374.

Laboratory activities  
No specific measures identified.

**Conditions and measures related to personal protection and hygiene**

**Section 3 - Exposure estimation and reference to its source**

**Website:** : Not applicable.

**Exposure estimation and reference to its source - Environment: 1: Coatings**

**Exposure assessment (environment):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

**Exposure estimation and reference to its source - Workers: 0: Coatings**

**Exposure assessment (human):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

**Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES**

**Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Health** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Additional good practice advice beyond the REACH CSA**

**Environment** : Not available.

**Health** : Not available.

## Annex to the extended Safety Data Sheet (eSDS)

Industrial

### Identification of the substance or mixture

**Product definition** : Mono-constituent substance  
**Code** : 35025  
**Product name** : ACETONE

### Section 1 - Title

**Short title of the exposure scenario** : [200-662-2] Uses in Coatings - Professional

**List of use descriptors** : **Identified use name:** Use in coatings - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC10, PROC11, PROC13, PROC15, PROC19  
**Sector of end use:** SU22  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08a, ERC08b, ERC08d, ERC08f  
**Market sector by type of chemical product:** Not applicable.  
**Article category related to subsequent service life:** Not applicable.

**Environmental contributing scenarios** : **Use in coatings**

**Health Contributing scenarios** : **Use in coatings**

**Processes and activities covered by the exposure scenario** : Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### Section 2 - Exposure controls

#### Contributing scenario controlling environmental exposure for 0: Use in coatings

**Product characteristics** : Substance is a unique structure., Ketone., Readily biodegradable  
**Amounts used** : Annual site tonnage 641  
**Frequency and duration of use** : Emission days 360  
**Other conditions affecting environmental exposure** : Indoor or outdoor use  
**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil** : Common practices vary across sites thus conservative process release estimates used.  
**Organizational measures to prevent/limit release from site** : Common practices vary across sites thus conservative process release estimates used.  
**Conditions and measures related to external treatment of waste for disposal** : External treatment and disposal of waste should comply with applicable local and/or national regulations.  
**Conditions and measures related to external recovery of waste** : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Date of issue/Date of revision** : 09/03/2016

**Contributing scenario controlling worker exposure for 0: Use in coatings**

<b>Concentration of substance in mixture or article</b>	: Covers percentage substance in the product up to 100% (unless stated differently).
<b>Physical state</b>	: Liquid, vapour pressure > 10 kPa
<b>Frequency and duration of use</b>	: Covers daily exposures up to 8 hours
<b>Other conditions affecting workers exposure</b>	: Assumes a good basic standard of occupational hygiene is implemented

**Contributing scenarios - Operational conditions and risk management measures**

General exposures (Eye irritation)  
Use suitable eye protection.

General exposures (skin Irritant)  
Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

General exposures (closed systems)  
Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.

Process sampling  
No specific measures identified.

Mixing operations (open systems) With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Mixing operations (open systems)  
Ensure operation is undertaken outdoors.

Mixing operations (open systems)  
Avoid carrying out activities involving exposure for more than 4 hours.

Bulk transfers Non-dedicated facility With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Bulk transfers Non-dedicated facility  
Ensure operation is undertaken outdoors.

Bulk transfers Non-dedicated facility  
Avoid carrying out activities involving exposure for more than 4 hours.

Bulk transfers Dedicated facility  
No specific measures identified.

Small package filling Dedicated facility  
No specific measures identified.

Equipment cleaning and maintenance  
Ensure material transfers are under containment or extract ventilation.

Equipment cleaning and maintenance  
Limit the substance content in the product to 25%.

Equipment cleaning and maintenance  
Avoid carrying out operation for more than 4 hours.

Spraying or fogging With local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.

Spraying or fogging  
Limit the substance content in the product to 25%. Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours.

Spraying or fogging



Avoid carrying out activities involving exposure for more than 1 hour.

Spraying or fogging  
Wear a respirator conforming to EN140 with type A/P2 filter or better.

Dipping, immersion and pouring  
No specific measures identified.

Laboratory activities  
No specific measures identified.

Hand application - fingerpaints, pastels, adhesives  
Limit the substance content in the product to 25%. Wear suitable gloves tested to EN374.

Hand application - fingerpaints, pastels, adhesives  
Avoid carrying out operation for more than 1 hour.

#### Conditions and measures related to personal protection and hygiene

### Section 3 - Exposure estimation and reference to its source

**Website:** : Not applicable.

#### Exposure estimation and reference to its source - Environment: 1: Use in coatings

**Exposure assessment (environment):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

#### Exposure estimation and reference to its source - Workers: 0: Use in coatings

**Exposure assessment (human):** : Not available.

**EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE** : Not available.

### Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

**Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Health** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

### Additional good practice advice beyond the REACH CSA

**Environment** : Not available.

**Health** : Not available.